

3 AA BATTERIES

INTRINSICALLY SAFE DUAL-LIGHT™ FLASHLIGHT

XPP-5422GMXA

NIGHTSTICK®

Life Depends on Light™



DUAL-LIGHT

285-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation

IP-67
DUST/WATER
PROOF


HANDS-FREE
INTEGRATED
MAGNETS

ZONE 0

CLASS I
DIV 1



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



Powerful base magnet allows "hands-free" use

CERTIFIED



285 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5422GMX, UPC 0 1739880812 5

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- cETLus, ATEX, IECEx, CE, InMetro, KOSHA, UKCA

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- 210L, 14 hrs. runtime

FLOODLIGHT

- 130L, 20 hrs. runtime

DUAL-LIGHT

- 285L, 10 hrs. runtime

CANDELA

- 7,970

BEAM DISTANCE

- 187 m

WATER RATING

- IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.2 in (183 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 6.9 oz (196 g)

POWER SOURCE







- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Removable lanyard
- Instruction manual

FL1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	210 LUMENS	130 LUMENS	285 LUMENS
	14h	20h	10h
	187m		
	7970cd		
	2m		
	1m		

Bayco Products, Inc. XPP-5422GMXA
 640 S. Sanden Blvd.
 Wylie, TX 75098



Intertek



ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3
 CLASS II & III DIV 1 GRPS E-G T135C
 CLASS I ZONE 0 AEx ia IIC T3 Ga
 CLASS I M 1 Ex ia op is I Ma
 CLASS II 1 G Ex ia op is IIC T3 Ga

Ex ia op is I Ma
 Ex ia op is IIC T3 Ga
 Intertek ITS 13 ATEX27837X
 IECEx ITS 16.0067X
 UKEX: ITS21UKEX0264X
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell AA Alkaline

Conforms to:
 ANSI/UL STD 913, ANSI/UL
 60079-0, ANSI/UL 60079-11
 ANSI/ISA 60079-26

Certified to:
 CAN/CSA STD C22.2 No 157
 CAN/CSA STD C22.2 No 60079-0
 CAN/CSA STD C22.2 No 60079-11
 CSA STD C22.2 No 25



SEE INSTRUCTION MANUAL
 VOIR MANUEL

MFG MM-YY

