

SAWFISH™

BULLHEAD SAFETY® EYE PROTECTION

PFT BH26613PFT
PERFORMANCE FOG TECHNOLOGY



BH266G

Optional foam gasket for
Sawfish™ style glasses
*Optional see below

LENS Variable Tint Performance Fog Technology

FRAME Matte Black

DESCRIPTION

The Sawfish™ is a dielectric ultra-light full-frame design that boasts chiseled lines and sleek curvature. Featuring inset TPR on the nose bridge and temple ends, the Sawfish™ is truly adaptable to any environment. The BH26613PFT also features a PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is a permanent coating that prevents the formation of condensation on the lenses by absorbing the humidity drops.

BH26G - Optional foam gasket for all Sawfish™ styles.

FEATURES

- PFT - Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and evenly disperse it, providing clear, fog-free vision
- Variable tint lenses darken when exposed to UV light (outdoors) and return to original tint when UV light is removed (indoors)
- Dielectric/nonconductive construction
- Lightweight full-frame design

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.



MEETS ANSI/ISEA
Z87.1-2020
STANDARDS



MEETS
ANTI-FOG
STANDARD



ARC FLASH
TESTED TO
35 CAL/CM²



FREE FROM
METAL
COMPONENTS



ERGONOMIC FIT
RELIEVES
PRESSURE



ANTI-SCRATCH
HARD COAT
TREATED LENS



PERMANENT
HYDROPHILIC
COATING



TAPERED LENS
ELIMINATES
DISTORTION



FILTERS 99.9%
UVA/UVB/UVC
LIGHT RAYS



DARKEN WHEN
EXPOSED TO UV
LIGHT



PROVIDES SEAL
AGAINST DEBRIS
AND IMPACT

*Optional

- Dual 8 base curve lenses for full protection and visual correctness
- Inset TPR nose bridge and temple ends comfortably secure eyewear and prevent slippage
- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	WEIGHT	BASE CURVE	FRAME WIDTH	TEMPLE LENGTH	END OF TIPS WIDTH
Variable Tint PFT	88.5% to 13.7%	Full Frame	Matte Black	30 Grams	8	132 mm	123 mm	102 mm

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	810033292132	10810033292139	20810033292136

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com



Bullhead Safety®