

LI-ION RECHARGEABLE

DICATA™ INTRINSICALLY SAFE DUAL-LIGHT USB HEADLAMP

XPR-5562GX

NIGHTSTICK®

Life Depends on Light™



MAGMATE™ Magnetic Coupler
USB Rechargeable.




Enlarged front-mounted dual switches, easily toggle through the beam options with gloves on.



Low Profile for Visor Clearance, on most helmets & hard hats.



Dual-Light Technology, focused spotlight and area floodlight at the same time.



300 LUMENS



1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

LI-ION BATTERY

ITEM NUMBER/UPC

- XPR-5562GX, UPC 0 17398 80774 6

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- cULus, ATEX, IECEX, CE, NFPA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 275L, 6 hrs. runtime
 - LOW: 100L, 15 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 250L, 6 hrs. runtime
 - LOW: 100L, 15 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 300L, 5 hrs. runtime

CANDELA

- HIGH: 3,660

BEAM DISTANCE

- 120 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 1.25 in (31 mm)
 - WIDTH: 3.75 in (95 mm)
 - DEPTH: 1 in (25 mm)
 - WEIGHT: 5.8 oz (164 g) without battery

POWER SOURCE

- Integrated Li-ion

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Headlamp
 - Li-ion Battery
 - Heavy-duty rubber head strap
 - 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord
 - Instruction Manual

FL1 STANDARD	SPOT HIGH	FLOOD HIGH	DUAL-LIGHT
	275 LUMENS	250 LUMENS	300 LUMENS
	6h	6h	5h
	120m		
	3660cd		

Bayco Products, Inc. XPR-5562GX
 640 S. Sanden Blvd., Wylie, TX 75098
 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 UL listed for use with Bayco Li-ion Battery Pack 5562-BATT

cULus LISTED
 E 467756
 ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV 1 GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia op is IIC T4 Ga
 © II 1 G Ex ia op is IIC T4 Ga

Ex ia op is IIC T4 Ga
 DEMKO 20 ATEX 2267
 IECEX UL 20.0036
 -20°C ≤ Tamb ≤ +40°C
 3.7V/Cell 5562-BATT
 Um 4.2V

WARNING: Do not charge battery in a hazardous location
 WARNING: Do not replace battery when an explosive atmosphere is present

SEE INSTRUCTION MANUAL
 VOIR MANUEL

Meets Requirements of NFPA-1971-8.6 (2013)

MFG MM-YY
 US Patent 9,713,217



© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPR-5562-Series-20

